FLEX HYDROSTOP DSF 300
DECLARATION OF PERFORMANCES
T – 135

DECLARATION OF PERFORMANCES T – 135

Unique identification code of the product-type:	**FLEX HYDROSTOP DSF 300**
Intended use/es:	**Surface protection products – coating:** **Ingress protection (1.3), Moisture control (2.2), Increasing resistivity (8.2)**
Manufacturer:	**THRAKON S.A., Syngrou Av. 130, 11745 Athens**
System/s of AVCP:	**AVCP System 4**
Harmonized Standard:	**EN 1504 – 2 : 2004**
Notified Body:	**DQS HELLAS LTD, NB : 2423** **Certificate number : 2423 – CPR – 9903 – PROTECT**
Declared performances:	

Essential characteristics	Performances
Reaction to fire	**Euroclass F**
Adhesion strength by pull off test	**≥ 0,8 N/mm²**
Permeability to CO_2	**S_d > 50m**
Water vapour permeability	**Class I (permeable)**
Capillary absorption	**< 0,1 Kg/(m²h^{0,5})**
Release of dangerous substances	**NPD**

The performance of the product identified above is in conformity with the set of declared performances. The technical requirements and the performances of the products are documented in the Technical File of the products and in the Technical Data Sheets of the Company.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Version 4th
Oinofita, 01 – 02 – 2026

A. Antoniou
Quality Control Manager

