

CARMPAINT RP - 10 **ROAD MARKING PAINT**



DESCRIPTION

CARMPAINT RP-10 is a paint containing synthetic resins and chlorinated rubber. It is used as binder for reflective glass beads and has perfect adhesion and reflectivity on asphalt surfaces. The paint is simply and easily applied with the help of a road marking machine.

The glass beads should be dispersed on the freshly painted road line, which should be fluid. Use approximately 0.72 kg of glass beads per litre of paint.

APPLICATION FIELDS

On asphalt surfaces with the help of a road marking machine.

ADVANTAGES – CHARACTERISTICS

- Excellent adhesion and reflectivity on asphalt surfaces.
- The paint is simply and easily applied with a road marking machine.

SUBSTRATE PREPARATION – APPLICATION

Stir the paint well. The proportion of glass beads in the paint should be strictly adhered to. The glass beads should be dispersed on the painted surface before it dries. The paint should be diluted with **LS-702 SOLVENT** up to 10%. The asphalt must be free from oil and other

impurities before the application of the paint. Do not apply while raining and do not stamp on the surface for at least 30 min after application.

APPLICATION RATE

2-4 m²/kg

CARMYPAIN RP - 10 **ROAD MARKING PAINT**



DILUTION

The paint should be diluted with **LS-702 SOLVENT** up to 10%.

PACKAGING – SHADES

Available in plastic containers of 5kg and 10kg.
Available white and yellow colours.

STORAGE

CARMYPAIN RP-10 can be stored in tightly closed containers for a long time, in cool and dry places.

PRECAUTIONS

For information about safe use, storage and disposal of the product read the information on the label and in the most recent MSDS of the product, which is available upon request to the professionals.

The remains of the paints should not be disposed of together with domestic waste. Ask for advice from the local government with regard to the disposal and removal of waste.

Poisoning Centre Tel. No.: 210 77.93.777