

STATUS EMULSION COLORANT

Emulsion paint

STATUS EMULSION COLORANTS are a series of basic shades of emulsion paints intended for tinting all white emulsion and acrylic paints. Odorless and absolutely user- and environmentally friendly, they can be easily mixed, they have great coloring power and offer high coverage. The final resulting shade is highly resistant to detergents and alkalis, time and solar radiation. In the end you will have a rich matt surface that can withstand washing and maintain its beautiful appearance for a long time.



Advantages:

- Environmentally friendly product without solvents.
- Odorless.
- No ammonia contained.
- Easily mixed with emulsion and acrylic paints.
- Strong colorant power.
- Resistant to washing with detergents.
- Perfect coverage.
- Stable shade over time.
- Excellent workability.



TECHNICAL CHARACTERISTICS

Packaging:

Plastic containers
 • 180 ml
 • 375 ml
 • 750 ml

Color:

Available in 8 basic shades: Yellow, Red, Black, Blue, Brick Red, Green, Brown, Ochre.



Drying time:

- Touch dry
1 - 2 h
- Recoating
2 - 3 h

*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.

Dilution with water:

5-10 (% v.v.)

Application:

For interior use. Tinting all white emulsion and acrylic paints.

Consumption:

10 -13 m²/lt.

Application tools:

Brush, roller, or airless gun.

Storage:

Store in tightly closed container in a cool and dry place for 36 months of the date of production only if it has not been diluted.

V.O.C. class :

(a) Interior matt walls and ceilings (gloss < 25 at 60°) (W.B) V.O.C limit: 30 gr/lt
 Maximum V.O.C of product ready to use product: 29 gr/lt

FIELDS OF APPLICATION

Suitable for tinting all white emulsion and acrylic paints.

SUBSTRATE PREPARATION

The surface should necessarily be clean, dry, rigid and free from dust, mold and oil before application. Remove all loose or peeled old paints. If stucco is required, use STATUS 100% ACRYLIC PUTTY and after it has dried, sand and wipe well. In case of big cracks, use only one layer of the Light, White ready for use STATUS ONE COVER putty. No need for smoothing. New surfaces should be primed with STATUS ACRYLIC PRIMER, STATUS AQUADUR or GLX 292 FLEX PRIM. In case of fresh plaster or concrete, let it dry deep for at least 1 month before application. If you want to paint gyp-sum boards or apply an additional layer of water paint (with lime or adhesive) or paint dirty surfaces (nicotine, smut from radiators, smog, exhaust fumes, coffee, juice, graffiti, ink, marker, fungi, mold, humidity, oil, etc.), first apply STATUS DUR primer.

APPLICATION

Mix well the content of the container before use. Add the amount of STATUS EMULSION COLOURANT required for achieving the desired shade to the container of the white paint. Then stir well the content to achieve absolute and homogeneous incorporation of the basic shades into the final mixture. After application close the container well to preserve in good condition for future use. It can be stored in a tightly closed container without problems for a long time as long as it is not diluted. Painted surfaces should not be washed for at least 20-30 days after application. New plaster or concrete surfaces should be painted after 30-40 days.

APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

TOOL CLEANING

Immediately after use, drain excess paint thoroughly into the container and clean tools using warm soapy water. Do not dispose of washing waste water into the aquifer groundwater.

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

Technical characteristics	Units	Standard	Value
Viscosity	cP	EN ISO 2555	6400 – 8800
Density	g/mL	EN ISO 2811-1	1,42 ± 0,03
- OCHRE			1,36 ± 0,03
- YELLOW			1,42 ± 0,03
- BRICK RED			1,33 ± 0,03
- RED			1,34 ± 0,03
- BLACK			1,36 ± 0,03
- GREEN			1,41 ± 0,03
- BROWN			1,37 ± 0,03
- BLUE			
Gloss (60° C)	%	ISO 2813	≤3
Dilution	%		5-10
Recoating time	h		2 – 3
Drying time	h		1 - 2

*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version D: 18/07/2024