

STATUS RED LEAD MARINE PRIMER

Powerful thixotropic antirust primer for metal surfaces



STATUS RED LEAD MARINE PRIMER is a powerful antirust primer containing pure red lead oxide (100% red lead) and strong anticorrosive pigments. It is suitable for the effective protection of metal surfaces against oxidation and is also applied as a primer on wooden surfaces exposed in outdoor conditions (such as casings, trellises, windows etc.) as well as in highly oxidizing environment (e.g. wooden vessels). Its thixotropic nature ensures effortless application, superior spreadability, rapid drying, and strong adhesion. With outstanding mechanical strength and anti-corrosive features, it delivers enduring protection over time.



Advantages:

- Suitable for antirust protection of all metal surfaces.
- Exceptional antirust protection of wooden surfaces even under adverse environmental and oxidizing conditions.
- Thixotropic.
- Strong adhesion.
- Outstanding workability and spreadability.
- Perfect coverage.
- High performance.



TECHNICAL CHARACTERISTICS



Packaging:

Metallic containers
 • 0,5 kg
 • 0.75 kg
 • 5 kg



Color:

Available in orange.



Drying:

- To the touch
1 – 2 h
- Recoating
24 h

*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.



Dilution with white spirit or turpentine:

• 5 (% v/v)



Application:

For exterior use. Suitable for antirust protection of all metal surfaces and wooden surfaces exposed to harsh environments.



Consumption:

5 - 6 m²/lt



Application tools:

Brush or roller.



Storage:

In the original sealed container, in dry environment at temperatures between +5° C and +35° C for 12 months after the production date.



V.O.C. class :

A/g Primers (S.B). V.O.C. limit: 350 gr/lt.
 Maximum V.O.C. of product ready to use: 345 gr/lt
 Maximum thinning: 5% v/v.

FIELDS OF APPLICATION

Suitable for the protection of all metal surfaces and for application of alkyd paints, such as STATUS DUKO, STATUS RUSTBLOCK and STATUS DUROMETAL.

SUBSTRATE PREPARATION

The surface should necessarily be rigid, dry and free from dust, grease or rust for good adhesion. Remove all loose or peeled old paints. Surfaces previously painted with oil paint should be sanded and wiped thoroughly.

APPLICATION

Stir well the content of the container before use, dilute properly and apply 1-2 layers taking care over all difficult points of the surface, such as corners, hollows etc. After application, close the container tightly to maintain in good condition for future use. It can be stored in a tightly closed container for a long time.

APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

TOOL CLEANING

Immediately after use, clean the brush, or roll with WHITE SPIRIT and then with hot water and detergent. Do not empty washings into the groundwater.

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

Technical characteristics	Units	Standards	Value
Viscosity	sec	ASTM D 5125, ISO 2431	40 – 60
Density	g/ml	EN ISO 2811-1	2.19 ± 0.03
Dilution	%	-	Έως 5%
Recoating time	h	-	24
Drying time	h	-	1 - 2

*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version B: 26/07/2024