

## **STATUSPOOL** **SWIMMING POOL PAINT**



### **DESCRIPTION**

Special 2-component polyurethane-based paint which is highly resistant to sunlight as well as to acid or alkaline environment. Suitable for swimming pools.

It exhibits high adhesion and absolute waterproofing properties, while high elasticity protects the surface from pitting, peeling or chalking.

### **APPLICATION FIELDS**

Suitable for painting swimming pools, fountains and tanks.

### **ADVANTAGES – CHARACTERISTICS**

- Exceptional resistance to UV radiation, water as well as to acid and alkaline environment.
- Absolute waterproofing.
- Very good hardness.
- High elasticity prevents from pitting, peeling or chalking.
- Gloss final feel.

### **SUBSTRATE PREPARATION – APPLICATION**

Clean well the surface that will be painted and remove loose parts. If stucco is required, **STATUSPOX EG-10** epoxy stucco is recommended. In new swimming pools first apply **STATUSPOOL PRIMER** epoxy primer. Sand the surface after 24 hours and apply

**STATUSPOOL**, after mixing 2 volumes of component A with 1 volume of component B. Dilute with **LS-703 SOLVENT** by approximately 10% for brush or roller and with **LS-744 SOLVENT** by 15-20 % for spray gun application.

### **DRYING**

For film thickness 120gr/m<sup>2</sup>, 20°C:

- Surface: Touch dry after 1 hour.
- Deep dry: 6 days

### **APPLICATION RATE**

8-9 m<sup>2</sup>/lt (for dry film 60 μm thick)

# STATUSPOOL SWIMMING POOL PAINT



## APPLICATION TOOLS

Brush, roller, spray gun.

## CLEANING OF TOOLS

Clean with **GENERAL PURPOSE NITRO SOLVENT LS-735**.  
Do not pour the washing liquids on the ground.

## PACKAGING–SHADES

Component A is available in plastic containers of 4lt.  
Component B is available in plastic containers of 2lt.  
Available in white and light blue shades.

## STORAGE

**STATUSPOOL** can be stored in tightly closed containers for a long time, in cool and dry places. Lifespan of component A: 12 months. Lifespan of component B: 6 months. The containers of component B should not remain opened. When component B is opened, it should be used within a few days.

## PRECAUTIONS

For information about safe use, storage and disposal of the product read the information on the label and in the most recent MSDS of the product, which is available upon request to the professionals.

The remains of the paints should not be disposed of together with domestic waste. Ask for advice from the local government with regard to the disposal and removal of waste.  
Poisoning Centre Tel. No.: 210 77.93.777

*The technical information and guidelines in this brochure related to the application and end-use of THRAKON products are based on the Company's current expertise and experience on the products and are given in good faith provided they are properly stored, used and applied in accordance with the guidelines given by THRAKON. Given that we are unable to directly inspect the conditions that prevail at the worksite as well as the application of the product, the Company shall not provide any guarantee regarding the suitability of its products for any particular purpose and disclaims any legal responsibility that is based on written information in this brochure or on written or oral or otherwise provided recommendations and guidelines. By applying the product on a small surface, the users are advised to test the product's suitability for the intended application and purpose. THRAKON reserves the right to amend the properties of its products without prior notice. All orders are accepted only after acceptance of the above and under the Company's respective Trade Policy terms. This version of the technical data sheet automatically cancels any previous version.*