

FLOOR SEAL W

Resinous floor stabilizer

FLOOR SEAL W is a resinous, water-based floor stabilizer with high penetration capacity. It is applied to cement-based floors to prevent the formation of dust, while sealing the pores of the surface, thus minimizing its water absorbency. It is also used on brittle surfaces to stabilize them and improve their abrasion resistance. After application it becomes transparent, therefore, it does not affect the surface aesthetically.



Advantages:

- High penetrability.
- Stabilizes weak and brittle surfaces.
- Reduces the water absorbency of the surface.
- Excellent workability.
- Excellent coverage.



TECHNICAL CHARACTERISTICS

Packaging:

Plastic container
5kg & 20kg

Application:

For indoor and
outdoor applications.
For concrete and
cement-based floors.

Color:

White in the packaging.
After application, it
becomes transparent.

Storage:

Stored in its original, sealed
container in dry place at
temperatures between +5°C
and +35°C for 24 months
from its production date.

Consumption:

~100-200 g/m²
depending on
surface
absorption.

Application tools:

Brush, roller, or airless
gun.

FIELDS OF APPLICATION

FLOOR SEAL W is suitable for stabilizing, reducing the absorben-cy and increasing the surface hardness of:

- Cement-based floors
- Concrete

It is recommended for indoor and outdoor applications.

SUBSTRATE PREPARATION

Before the application it is recommended to sand the surface in order to open its pores and to ensure proper adhesion. Before applying FLOOR SEAL W ensure that the substrate is clean, free from brittle and foreign bodies residue, paint, oils, etc.

APPLICATION

Stir the contents of the container well before use. The temperature during application should be between +5°C and +35°C. FLOOR SEAL W is applied, without dilution, by airless gun, brush or roller, evenly until saturation. Where necessary (very absorbent substrates) a second coat is applied after the first coat has completely dried.

TOOL CLEANING

Immediately after use, drain the material in the box thoroughly and clean all tools with water. Do not dispose of washing waste water into the aquifer.

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

Technical characteristics	Units	Standard	Value
Form			Emulsion
Shade			White / transparent after application,
Density	kg/l		1,08
pH			9 - 11
Walkability	h		24
Final curing time	d		3-4

*Note: The measurements were taken in laboratory environment under normal temperature and relative humidity conditions (+23°C, 50%). It is possible for them to vary depending on the conditions prevailing at the worksite (temperature, humidity, absorbability of the substrate).

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version F: 03/04/2026