

ANTISLIP PROMOTER

Adhesion promoter

DECOR

ANTISLIP PROMOTER is a transparent, adhesion promoter with strong adhesion, one component suitable for indoor and outdoor use. It activates chemically the surface and provides excellent adhesion on glass and ceramic surfaces. The ANTISLIP PROMOTER is polymerized with the air and the ground humidity.



Advantages:

- Easy and fast application.
- High adhesion to the substrate.
- Resistance to UV radiation.
- Economic solution for perfect result.
- Matures quickly.



TECHNICAL CHARACTERISTICS

Packaging:

Plastic can 1 L

Application:

Indoor and outdoor use. Suitable for glass and ceramic surfaces, such as glass-ceramic tiles, glass, glass blocks etc.

Color:

Transparent mat.

Storage:

In the original, sealed packaging, in a dry environment at temperatures between +5°C and +35°C for 12 months from the date of production.

Consumption:

50 – 100 ml/m² on one or two layers based on a damp cloth coating.

Drying:

2 – 3 h

*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.

Application tools:

Wet cloth.

FIELDS OF APPLICATION

ANTISLIP PROMOTER is used as an adhesion promoter that chemically activates the surface before the application of ANTISLIP on glass and ceramic surfaces, such as glass-ceramic tiles, glass, glass blocks etc.

SUBSTRATE PREPARATION - APPLICATION

The substrate must necessarily be clean, dry and free of dust, mold and grease prior to the application. The substrate must be stable, all loose particles such as dust, oil, grease must be removed. Moreover, standing waters must be removed. The surface should be waterproofed and not subject to continuous rising damp. Also, the humidity of the substrate must be less than 4% and the atmospheric humidity less than 65%. Do not wash the surface with water.

Priming of inorganic non-absorbent surfaces (eg glass ceramic tiles, glass and glass blocks):

Prime the surfaces with the ANTISLIP PROMOTER primer by mopping them. Dampen a clean cloth with a rich amount of ANTISLIP PROMOTER and clean the entire surface. Change the cloth often. In this way the surface is chemically activated by simultaneously increasing the adhesion and removing the surface fats. It is important that the ANTISLIP PROMOTER spreads over the entire surface. It can be recoated after 2-3 hours.

The consumption of ANTISLIP PROMOTER is based on a damp cloth coating on a smooth surface under normal laboratory conditions. Factors such as substrate absorbency, temperature, relative humidity and mode of application can change the recommended consumption.

TIPS

- The adhesion promoter ANTISLIP PROMOTER and the 2-component anti-slip varnish ANTISLIP must be placed in 24 hours to achieve the best adhesion between them.
- Surfaces already impregnated with silicone, siloxane or silane impregnation materials should be tested to achieve better adhesion.
- The product and its vapors are flammable. Protect your breathing, eyes and skin. Keep away from children. Keep away from heat and other sources of ignition.

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining product should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste. [Poisons Information Call Center 210 77.93.777](tel:2107793777)

*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version B: 30/01/2026