

STONE VARNISH

Acrylic stone varnish

STATUS STONE VARNISH is a colorless, protective and decorative stone varnish. It is suitable for interior and exterior use on natural porous (Karystou, Piliou tiles, etc.) or artificial stones and other artificial building materials (bricks, roof tiles, etc.). It is specially formulated to penetrate deep into the surface pores forming a waterproof membrane that prevents the formation of mold while enhancing the natural color of the material. It does not peel and turn yellow and leaves a lovely glossy surface that can withstand harsh weather conditions for a long time. Thanks to advance UV filters, it offers exceptional protection against intense sunlight.



Advantages:

- Excellent waterproofing.
- Prevents the formation of mold.
- Exceptional durability against yellowing
- Enhances the natural color of the structural element.
- It gives a lovely glossy surface.
- Robust protection against mechanical wear, frictional damage, corrosion, and airborne pollutants.



TECHNICAL CHARACTERISTICS

Packaging:

Metallic containers
• 0,75 lt
• 2,5 lt

Color:

Colorless.

Application:

For exterior and interior use.
Ceramics, Marbles, Bricks, Granite, Terraces, Fireplaces, Walls, Mosaics, etc.

Consumption:

10-12 m²/lt

Drying:

- To the touch
1-1.5 h
- Recoating
3-4 h

*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.

Application tools:

Brush, roller or airless gun.

Storage:

Store in tightly closed container for 36 months of the date of production in a cool and dry place.

V.O.C. class :

A/h Binding primers (S.B.). V.O.C. limit : 750 gr/ Maximum V.O.C. of product ready to use: 749 gr/lt
Maximum thinning: Ready to use.

FIELDS OF APPLICATION

Suitable for interior and exterior use on :

- Natural or artificial stones, ceramics, marbles, bricks, granite, limestone, Karystos, Pilio, Malta tiles, etc.
- Terraces, fireplaces, walls, mantels, mosaics, concrete, plaster, etc.

SUBSTRATE PREPARATION

The surface must be dry, sound and free from dust, rust, oil and other materials.

APPLICATION

The first coat is applied undiluted. Once thoroughly dry, after 3-4 hours, apply a second coat to ensure more durability and sheen. Close the container tightly after use to keep the paint in good condition for future use. Can be stored in a tightly sealed container for a long time.

APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

TOOL CLEANING

Clean all tools with WHITE SPIRIT immediately after use and then with hot water and detergent. Clean the spray with LS-735 NITRO THINNER. Do not dispose of washing waste water into the aquifer.

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

Technical characteristics	Units	Standard	Value
Viscosity	sec	ASTM D 5125, ISO 2431	26 - 33
Density	g/ml	EN ISO 2811-1	0.85 ± 0.03
Dilution	%	-	Ready to use
Recoat time	h	-	3 – 4
Drying time	h	-	1 – 1.5

*Note: Measurements have been performed in a laboratory environment under standard conditions of humidity and temperature (+23°C, 50%). The values may differ depending on the conditions prevailing on the construction site (temperature, humidity, substrate absorbency).

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version B: 25/07/2025