



FLOORING SCREEDS

FLOORING MORTARS
AND SCREEDS
FOR SMOOTH SURFACES
AND HIGH HARDNESS

We build together
for a better living.





**Welcome to a world full of high quality,
aesthetics and excellent service...
in the world of THRAKON!**

The real experience of building materials and premium colors. Utilizing long-term experience and know-how, THRAKON is one of the largest research and production companies in the building materials, paints and varnishes industry. THRAKON has the ability to provide integrated services and solutions for a wide range of applications.

BRANDS

THRAKON has an active presence in the market with the following leading brands.

CLIMA PLUS

STATUS

DECOR

ULTRAPOR[®]

DESMOFLEX[®]

CARMYFIX[®]

**REPI
FIX**

Why THRAKON?





Reliability

THRAKON is one of the most reliable producers of mortars in Greece with guaranteed steady supply and six production facilities.



Quality

We offer products, services and solutions of the highest quality which add value to our customers.



Responsibility

THRAKON, since its foundation, presents in market high quality products and integrated solutions, that are innovative, environmentally friendly and economically profitable for the industry. We operate a continuous and reliable business strategy for our clients in order to justify and maintain their trust in us.



Technical Support

THRAKON recognizing the importance of after sales services, is committed to provide complete solutions and advice from specialized engineers and experienced applicators. We want always be close to the customer with a high sense of responsibility.





FLOORING SCREEDS

CEMENT BASED FLOORING SCREEDS

PRIMERS

CEMENT BASED FLOORING SCREEDS



NSD 600

Cement-based floor screed 3 - 10 cm

NSD 600 is a ready to mix, cement-based mortar suitable for floor filling and leveling. Consists of selected quartz sand of 2.5mm maximum grain size.



Applied at thickness of 3-10 cm. Recommended for: creation of inclinations of flat roofs and outdoor places, ramps, preparation of concrete floors for the installation of any type of tile, marble, decorative materials or parquet, indoor and outdoor areas.



Exterior & Interior use



15 - 17 kg/m² of dry mortar for 1 cm thickness



60 Items (25 kg)
35 Items (40 kg)



Code	Pkg
P11902025	25 kg
P11902040	40 kg



NSF 610

Self-levelling floor screed up to 10 mm

NSF 610 is a self-levelling, cement based mortar for the smoothing and levelling of floors. Consists of cement, quartz sand of 0.5 mm max. grain and admixtures.



Applied at a thickness of up to 10 mm. Suitable for construction of selfleveling floors, for preparation in order to install wall to wall carpeting, tiles, plastic or wooden floors glued or not. Final applied surface can be left completely uncovered or painted.



Exterior & Interior use



18 kg/m² for 1 cm thickness



60 items (25 kg)



Code	Pkg
P11903125	25 kg



NSF 611

Self-levelling floor screed 1 - 4 cm

NSF 611 is a self-levelling, cement based mortar for floor smoothing and levelling. It consists of cement, quartz sand of 3.5 mm max. grain and admixtures.



Applied at a thickness of 1 - 4 cm. Suitable for construction of self-levelling floors, for preparation in order to install wall to wall carpeting, tiles, plastic or wooden floors glued or not. Final applied surface can be left completely uncovered or painted.



Exterior & Interior use



18 kg/m² for 1 cm thickness.



60 items (25 kg)



Code	Pkg
P11903225	25 kg



NSH 650

Surface hardener

NSH 650 is a cement-based, polymer-modified, surface hardener for flooring screeds.



Suitable for floor applications that require high mechanical strengths. Consists of cement, quartz sand, pigments and additives.



Exterior & Interior use



3 - 5 kg/m²



60 items (25 kg)
35 items (40 kg)



Code	Pkg	Shade
P11900125	25 kg	Grey
P11900040	40 kg	Grey

PRIMERS

**FLOOR SEAL S****Curing compound with antievaporation agent for concrete floors**

1-component, solvent-based, clear acrylic resin polymer. The unique composition of the product: protects the fresh concrete from rapid evaporation of mixing water, hardens the existing brittle floors to increase their abrasion and wear resistance, enhances the maturation of concrete in order to avoid cracks and dryness, and seals the concrete to avoid dust.



Ideal for areas that are subject to moisture but with light traffic such as basements, parking lots, warehouses, and for large exposed concrete surfaces, such as industrial floors, parking spaces, concrete slabs.



Exterior &
Interior use



110 - 210 mL/m² per layer
(depending on the absorbency
of the substrate)



72 items (4 L)
24 items (20 L)

Code	Pkg	Shade
P21902104	4 L	Transparent
P21902120	20 L	

**FLOOR SEAL W****Resinous floor stabilizer**

Resinous floor stabilizer, water-based, with high penetration capacity. It is applied to cement floors to prevent the creation of dust while at the same time sealing the pores of the surface, thus minimizing its absorbency. It is also used on friable surfaces to stabilize them and improve their abrasion resistance. After its application, it becomes transparent and thus does not aesthetically alter the surface.



Suitable for stabilizing, reducing absorbency and increasing the surface hardness of cement mortar and concrete floors.



Exterior &
Interior use



100 - 200 g/m² per layer
(depending on the absorbency
of the substrate)



72 items (5 kg)
24 items (20 kg)

Code	Pkg	Shade
C/C	5 kg	Transparent
C/C	20 kg	



ICON MEMO



Interior and exterior use



Exterior use



Interior use



Application



Delivery time



Dimensions



Weight



Consumption



Items per pallet



Items per box



Shades



Also provided in silo



Coefficient of thermal conductivity

C/C

Where C/C appears,
call us to provide you with
the code of the product.



CERTIFICATIONS / SYSTEMS

C1 With normal characteristics, for absorbent tiles and common substrates - Exterior & Interior use.	CG2 WA With enhanced features for demanding applications, with high abrasion resistance, low water absorption and low shrinkage - Exterior & Interior use.	 Fire protection class A2
C1T With normal characteristics, for absorbent tiles and normal substrates - with zero vertical slip - Exterior & Interior use.	D2TE Dispersion adhesive with enhanced characteristics for all types of tiles, with zero vertical slip and extended open time - Exterior & Interior use.	 Certification of the external thermal insulation system.
C1TE With normal characteristics for absorbent tiles and common substrates. With slip resistance and extended open time - Exterior & Interior use.	R2T Epoxy-based glue with reinforced characteristics for all types of tiles and with zero vertical slip - Exterior & Interior use.	 European Standard EN 13499 for the thermal insulation system.
C2T With enhanced features for non-absorbent tiles and zero vertical slip - Exterior & Interior use.	S1 With enhanced features for non-absorbent tiles, with zero vertical slip and extended open time - Very Elastic - Exterior & Interior use.	 Standard requirements for cementitious grouts.
C2E With enhanced features for non-absorbent tiles and extended open time - Exterior & Interior use.	S2 With enhanced features for non-absorbent tiles, with zero vertical slip and extended open time - Super Elastic - Exterior & Interior use.	 Standard requirements for Expanded Polystyrene (EPS) according to the performance of the material in strength.
C2TE With enhanced features for non-absorbent tiles, with zero vertical slip and extended open time - Elastic - Exterior & Interior use.	CE The CE marking is the mark of product quality. Its existence ensures for the consumer that the characteristics of the product he has chosen correspond to the European characteristics established for the product.	 Harmonized standard for external and internal coatings.
 EU Ecolabel for products that meet strict ecological criteria.	 Fiber reinforced product	 A product that can be used in the CLIMAPLUS external thermal insulation system.
 Environmental Product Declaration: Official and verified document recording the environmental impacts of a product throughout its life cycle, according to international standards.	 25 years expected working life	

Headquarters

130 Siggrou Avenue
Athens -11745
7th floor

Customer Service

+30 210 36 33 512
sales@thrakon.gr

Technical Support

+30 210 36 33 512
info@thrakon.gr

Join us at:

/ Thrakon.Greece
/ company / thrakon-group

/ thrakon.greece
/ THRAKONGreece

We build together.

www.thrakon.gr